

Declaration of Performance

Nr.: DOP – 3 – FT PERFECT FINISH - 01

1.	Unique identification code of the product type:	P – 3 – FT PERFECT FINISH
2.	Product:	FibaTape® Perfect Finish
3.	Intended use of construction product:	Glass fibre joint tape for gypsum plasterboards
4.	Manufacturer:	SAINT-GOBAIN ADFORS CZ, s.r.o. Sokolovská 106 570 01 Litomyšl The Czech Republic
5.	System of assessment:	System 3
6.	Technical Assessment Body:	TECHNICKÝ A ZKUŠEBNÍ ÚSTAV STAVEBNÍ PRAHA, s. p. notified body 1020
	European Technical Assessment:	ETA 09/0075 of 03.03.2023
	European Assessment Document:	EAD 070002-00-0505: 2016

Declared performance:

Essential characteristics	Performance	Harmonized technical specification
Reaction to fire	NDP	EAD 070002-00-0505: 2016
Tensile strength (standard conditions 23 ± 1 °C)	$\sigma_k = 20,7$ N/mm	
Resistance to dampness	$\sigma_k = 20,2$ N/mm; 2%	
Self-adhesion ability (low temperature conditioning at -10 °C for 24 hours)	no visual changes and other defects	
Self-adhesion ability (high temperature conditioning at 70 °C for 24 hours, relative humidity 50 ± 5 %)	up to 5 % of peeled area of tested sample	
Jointing material penetration ability	75 N	

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.


Signed for and on behalf of the manufacturer by:

In Litomyšl, date 13.03.2023

.....

 Jana Kršková
 Product Manager

CE mark:

	
09	
CZ00012661	
Sokolovská 106, 570 01 Litomyšl, The Czech Republic	
Identification code: P – 3 – FT PERFECT FINISH	
Ref. nr. of DoP: DOP – 3 – FT PERFECT FINISH – 01	
<h2>FibaTape® Perfect Finish</h2>	
Glass fibre joint tape for gypsum plasterboards	
Essential characteristics	Performance
Tensile strength (standard conditions 23 ± 1 °C)	$\sigma_k = 20,7 \text{ N/mm}$
Resistance to dampness	$\sigma_k = 20,2 \text{ N/mm}; 2\%$
Self-adhesion ability (low temperature conditioning at -10 °C for 24 hours)	no visual changes and other defects
Self-adhesion ability (high temperature conditioning at 70 °C for 24 hours, rH = 50 ± 5 %)	up to 5 % of peeled area of tested sample
Jointing material penetration ability	75 N
European Assessment Document: European Technical Assessment: Notified body:	EAD 070002-00-0505 ETA 09/0075 1020