

# Declaration of Performance

Gyproc® EasiFill 45



<b>1 Unique identification code of the product type:</b>	Gyproc EasiFill 45
<b>2 Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):</b>	Gyproc EasiFill 45 EN 13963:2005 3B For product expiring 4th March 2026 onwards
<b>3 Intended use/s:</b>	Gypsum based material for filling and finishing joints in plasterboard systems
<b>4 Manufacturer:</b>	British Gypsum Registered in England 734396 East Leake, Loughborough, Leicestershire LE12 6HX Tel: +44 (0) 115 945 1000
<b>5 Authorised representative:</b>	N/A
<b>6 System/s of AVCP:</b>	System 4 generally System 3 Reaction to Fire
<b>7 Designated standard:</b> <b>Approved body/ies:</b> <b>Performed:</b> <b>Under:</b>	EN 13963:2005 Warrington Fire (AB 0833) Reaction to Fire System 3
<b>8 UK Assessment Document:</b> <b>UK Technical Assessment:</b> <b>Technical Assessment Body:</b> <b>Approved body/ies:</b>	N/A N/A N/A N/A
<b>9 Declared performance/s:</b>	The characteristics in the table below apply to all products mentioned in 2 above.

Essential characteristics	Performance	Harmonised technical specification
Reaction to Fire (R2F)	A1	EN 13963:2005
Flexural strength (F)	NPD	EN 13963:2005

## 10 Appropriate Technical Documentation and/or Specific Technical Documentation:

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulations (EU) No. 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Dean O'Sullivan, Managing Director, British Gypsum

East Leake 15/10/2025

Place and date of issue